

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 April 2005 (14.04.2005)

PCT

(10) International Publication Number  
**WO 2005/033644 A2**

Best Available Copy

(51) International Patent Classification<sup>7</sup>: **G01L 1/00**

(21) International Application Number:  
PCT/IB2004/003173

(22) International Filing Date:  
29 September 2004 (29.09.2004)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:  
TO2003A000774 3 October 2003 (03.10.2003) IT  
TO2003A000775 3 October 2003 (03.10.2003) IT

(71) Applicant (for all designated States except US): **C.R.F. SOCIETÀ CONSORTILE PER AZIONI** [IT/IT]; Strada Torino, 50, I-10043 Orbassano (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PULLINI, Daniele** [IT/IT]; c/o C.R.F. Società Consortile per Azioni, Strada Torino, 50, I-10043 Orbassano (Torino) (IT). **PERLO, Piero** [IT/IT]; Via Chichignolo, 19, I-12048 Sommariva Bosco (IT).


(74) Agents: **NOTARO, Giancarlo**, et al.; Buzzi, Notaro & Antonielli d'Oulx Srl, Via Maria Vittoria 18, I-10123 Torino (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **MAGNETIC TRANSDUCTION SENSOR DEVICE, MANUFACTURING PROCESS AND DETECTION PROCESS THEREFORM**



(57) Abstract: Magnetic pressure sensor device, of the type comprising at least one magnetic layer (11) able to vary a magnetisation associated thereto in response to a pressure (P) exerted thereon. Said device (20; 30; 40; 50) comprises a plurality of layers (11, 12, 13, 14, 15, 16, 17) arranged in a stack, said magnetic layer (11) able to vary a magnetisation associated thereto in response to a pressure (P) comprising a free magnetic layer (11), able to be associated to a temporary magnetisation (MT), said free magnetic layer (11) belonging to said plurality of layers (11, 12, 13, 14, 15, 16, 17), which further comprises at least a spacer layer (13; 23; 33) and a permanent magnetic layer (12) associated to a permanent magnetisation (MP). Said sensor device (20) further comprises a compressible layer (21; 31; 42) and a layer with high magnetic coercivity (22; 32; 42) associated to said plurality of layers (11, 12, 13, 14, 15, 16, 17).

WO 2005/033644 A2



**Published:**

— without international search report and to be republished upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

Best Available Copy